



## **AN-ISE sc Low cost ISE combination Ammonium and Nitrate probe (immersion) without RFID, 10 m cable**

Ürün Numarası: **LXV440.99.00011**  
TRY Fiyat: **Bize Ulaşın**

### **AN-ISE sc: Combination sensor for ammonium and nitrate**

Carries out continuously direct measurements using an ion-selective electrode. No need for reagents or sample preparation. Compensated interference by potassium and chloride.

The special feature of the probe is the Cartrical technology. This provides reliable measured values and considerably reduced maintenance time and costs in comparison with conventional ISE probes.

The complete system - SC controller has to be ordered separately - comes from a single supplier. The probe is installed on the side of the tank. The measuring system can be extended to include an automatic cleaning unit with a compressor.

Prognosys is a predictive diagnostic system that allows you to be proactive in your maintenance, by alerting you to upcoming instrument issues. Know with confidence whether changes in your measurements are due to changes in your instrument or your water.

This instrument connects to Claros, Hach's innovative Water Intelligence System, enabling you to seamlessly connect and manage instruments, data, and process – anywhere, anytime. The result is greater confidence in your data and improved efficiency in your operations. To unlock the full potential of Claros, insist on Claros Enabled instruments.

### **Trustable results for ammonium and nitrate**

Looking for new ways to stretch money and reduce consumable cost? We have the perfect solution for you! Our new combination sensor with ion-selective electrode (ISE) technology was developed to measure both  $\text{NH}_4$  and  $\text{NO}_3$  at the same spot. What is unique? The most significant interferences of K and Cl are simultaneously compensated by integrated ISE electrodes, ensuring accurate results 24h/7days.

### **Easy handling with Cartrical cartridge plus**

The compact Cartrical cartridge contains four electrodes which are calibrated to each other before leaving the factory. Through the newly developed Cartrical plus technology, the factory calibration is automatically identified after replacing the cartridge. The compact design does away with tiresome handling and adjustment of individual electrodes: just unscrew the old cartridge, plug in the new one and the sensor is immediately ready to measure.

### **Simple and intuitive operation**

With a menu-guided operation and step-by-step guide with clear text, the combination AN-ISE sc sensor is very easy to use. It works directly with every SC controller without complicated wiring or set up procedures: just plug and play. The common SC controller platform allows intuitive usage not only for ammonium and nitrate but also for other parameters like pH, DO, etc.

### **Always under control**

In combination with SC 1000 controller, alert messages from AN-ISE sc sensor can be transmitted to the control room or by SMS / e-mail to a mobile phone. You are always informed about the status of your processes, early enough to react quickly.

### **Rely on Hach's application know how**

You can trust our ISE experience gathered in many waste water applications around the world. Based on this we have developed the next ISE generation to fulfil your requirements even better. Our application team is always close by.

Ağırlık:	2.38 kg
Akış:	< 4 m/s max. velocity
Daldırma derinliği:	0.3 - 3.0 m
	max. 0.3 bar (4.4 psi) pressure
Doğruluk:	5% of measured value +0.2 mg/L (with standard solutions) NH <sub>4</sub> -N and NO <sub>3</sub> -N
İçerik:	Ammonium & Nitrate probe, sensor cartridge, user manual
İşletme sıcaklık aralığı:	Air: -20 - 45 °C (-4 - 113 °F)
Kablo Uzunluğu:	10 m (32.8 ft) fixed cable at sensor, available up to 100 m
Kalibrasyon metodu:	Factory calibrated sensor cartridge (Cartrical), 1 and 2 point matrix correction
Kontrol ünitesi uyumluluğu:	SC200, SC1000, SC4500. All controllers sold separately
Koruma sınıfı:	IP68
Kurulum:	45 ° ± 15 ° (vertical in flow direction)
Kutudakiler:	Ammonium & Nitrate probe, sensor cartridge, user manual
Malzeme:	Cartridge: stainless steel (1.4571), PVC, POM, ABS, NBR
	Cleaning unit: TPE, PUR, stainless steel (1.4571)
	Sensor: stainless steel (1.4571), ASA + PC, silicon, PVC and PU
Numune basıncı:	0.3 bar max.
Numune sıcaklığı:	2 - 40°C (35,6 - 104°F)
Ölçüm aralığı:	0 - 1000 mg/L NH <sub>4</sub> -N
	0 - 1000 mg/L NO <sub>3</sub> -N
	0 - 1000 mg/L K <sup>+</sup>
	0 - 1000 mg/L Cl <sup>-</sup>
Ölçüm belirsizliği:	± 5 % of the measured value + 0.2 mg/L (with standard solution) NH <sub>4</sub> -N and NO <sub>3</sub> -N
Ölçüm metodu:	Potentiometric ion-selective electrodes for ammonium, potassium, nitrate and chloride, reference system and temperature sensor
Ölçüm sıklığı:	Continuous
Parametre:	Ammonium, Nitrate
pH Aralığı:	5 - 9 pH
Proses bağlantısı:	1 inch thread
Saklama koşulları:	5 - 40 °C sensor cartridge
Saptama limiti:	0.2 mg/L NH <sub>4</sub> -N and NO <sub>3</sub> -N
Sensör kartuşu:	With Cartrical plus technology: compact housing containing calibrated electrodes for ammonium, potassium, nitrate and chloride, reference system and temperature sensor, all calibrated to each other; typical lifetime 12 months
Tekrarlanabilirlik:	± 5 % ölçülen değerin (standart solüsyonla) NH <sub>4</sub> -N
Tepki süresi:	< 3 min
Uzunluk:	320 mm
Veri türleri:	Current output, relays and bus communication via SC controller

---

## Kutudakiler

Ammonium & Nitrate probe, sensor cartridge, user manual

## Gerekli Aksesuarlar

- SC1000 Ekran Modülü (Item LXV402.99.00001)
- SC4500 Kontrol Ünitesi, 5x mA Çıkış, 2 dijital sensör, fişsiz (Item LXV525.99A01551)
- SC4500 Kontrol Ünitesi, Prognosys, 5x mA Çıkış, 2 dijital sensör, 100 - 240 VAC, güç kablosu bulunmamaktadır (Item LXV525.99A11551)
- SC4500 Kontrol Ünitesi, Claros uyumlu, 5x mA Çıkış, 2 dijital sensör, 100 - 240 VAC, güç kablosu bulunmamaktadır (Item LXV525.99AA1551)
- SC4500 Kontrol Ünitesi, Claros uyumlu, 5x mA Çıkış, 2 dijital sensör, 100 - 240 VAC, AB tipi fiş (Item LXV525.99CA1551)
- SC4500 Kontrol Ünitesi, Prognosys, 5x mA Çıkış, 1 dijital Sensör, 100 - 240 VAC, güç kablosu bulunmamaktadır (Item LXV525.99A11501)
- SC4500 Kontrol Ünitesi, Prognosys, 5x mA Çıkış, 1 dijital Sensör, 100 - 240 VAC, AB tipi fiş (Item LXV525.99C11501)
- SC4500 Kontrol Ünitesi, Prognosys, 5x mA Çıkış, 2 dijital Sensör, 24 VDC, fişsiz (Item LXV525.99Z11551)