



EZ1009 Chromium Cr(VI) Analyser

Ürün Numarası: EZ1009.XXXXXXXX

TRY Fiyat: Bize Ulaşın

Online colorimetric analysis of dissolved Chromium Cr(VI) in water

EZ1000 Chromium Cr(VI) Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low $\mu g/L$ range.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator invervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Chromium Cr(VI) Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Teknik özellikler

Ağırlık: 25 kg

Akış Hızı: 100 - 300 mL/min

Alarm: 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts

Analog çıkışlar: Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)

Boyut (Y x G x D): 690 mm x 465 mm x 330 mm

Cihaz havası: Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air

Demineralize su: For rinsing / dilution

Dijital çıkışlar: Optional: Modbus (TCP/IP, RS485)

Doğrulama: Automatic; frequency freely programmable

Doğruluk: Better than 2% full scale range for standard test solutions

Drenaj: Atmospheric pressure, vented, min. Ø 32 mm

Enerji: 100 - 240 VAC, 50/60 Hz

Max. power consumption: 120 VA

Garanti: 24 aylar

Girişimler: Iron (III), Mercury > 200 mg/L, Molybdenum > 200 mg/L, Vanadium (V) > 5 mg/L.

Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.

Güç kaynağı: 100 - 240 VAC, 50/60 Hz

Kalibrasyon: Automatic, 2-point; frequency freely programmable

Koruma sınıfı: Analyser cabinet: IP44 / Panel PC: IP65

Kutudakiler: EZ1009 Chromium Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting

Brackets, 1 x empty 2.5L Glass Reagent Container with Fittings (for Colour) and 1 x empty 5L

Reagent Container with Fittings (for Buffer Solution)

Malzeme: Hinged part: Thermoform ABS, door: PMMA

Wall section: Galvanised steel, powder coated

Model: EZ1009

Numune akışı sayısı: 1, 2, 4, or 8

Numune basıncı: By external overflow vessel

Numune kalitesi: Maximum particle size 100 μm, < 0.1 g/L; Turbidity < 50 NTU

Numune sıcaklığı: 10 - 30 °C

Ölçüm aralığı: 5 - 500 μg/L Cr(VI)

Optional:

 $1 - 50 \mu g/L Cr(VI)$

 $2 - 125 \mu g/L Cr(VI)$

2.5 - 250 µg/L Cr(VI)

0.08 - 2 mg/L Cr(VI) (with internal dilution)

0.16 - 4 mg/L Cr(VI) (with internal dilution)

0.5 - 50 mg/L Cr(VI) (with internal dilution)

Ölçüm metodu: Colorimetric measurement at 546 nm using diphenylcarbazide method, conform with standard

method APHA 3500-Cr (B)

Ölçüm süresi: 10 min (dilution + 5 min)

Ortam sıcaklığı: 10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)

Otomatik temizleme: Evet

Parametre: Chromium Cr(VI), dissolved

Reaktif gereksinimi: Keep between 10 - 30 °C

Saptama limiti: $\leq 1 \mu g/L$

Sertifikalar: CE compliant / ETL certified

Toprak bağlantısı: Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²

Kutudakiler
EZ1009 Chromium Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x empty 2.5L Glass Reagent Container with Fittings (for Colour) and 1 x empty 5L Reagent Container with Fittings (for Buffer Solution)
Product details pdf footer