



## EZ2000 Total Aluminium Analyser

Ürün Numarası: EZ2000.XXXXXXXXXX  
TRY Fiyat: Bize Ulaşın

### Online colorimetric analysis of Total Aluminium in water

EZ2000 Total Aluminium Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

EZ2000 Total Aluminium Analysers have an internal digestion unit. This additional step prior to analysis allows to measure non-soluble or complexed metal species.

### Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

### Flexibility that meets your needs

EZ Series Aluminium Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

---

### Teknik özellikler

Ağırlık:	25 kg
Akış Hızı:	100 - 300 mL/min
Alarm :	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Analog çıkışlar:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Boyut (Y x G x D):	690 mm x 465 mm x 330 mm

Cihaz havası:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Demineralize su:	For rinsing / dilution
Dijital çıkışlar:	Optional: Modbus (TCP/IP, RS485)
Doğrulama:	Automatic; frequency freely programmable
Doğruluk:	Better than 2% full scale range for standard test solutions
Drenaj:	Atmospheric pressure, vented, min. Ø 32 mm
Enerji:	230 VAC, 50/60 Hz
	120 VAC, 50/60 Hz
	Max. power consumption: 440 VA
Garanti:	24 aylar
Girişimler:	Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Kalibrasyon:	Automatic, 2-point; frequency freely programmable
Koruma sınıfı:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65
Kutudakiler:	EZ2000 Aluminum Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, and 4 x empty 2.5L Reagent Containers with Fittings 2.5L (for Acid, Buffer, Colour & Mixed Reagent Solution)
Malzeme:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated
Model:	EZ2000
Numune akışı sayısı:	1, 2, 4 or 8
Numune basıncı:	By external overflow vessel
Numune sıcaklığı:	10 - 30 °C
Ölçüm aralığı:	10 - 150 µg/L Al
	Optional:
	10 - 75 µg/L
	80 - 600 µg/L (with internal dilution)
	160 - 1500 µg/L (with internal dilution)
	1000 - 3000 µg/L (with internal dilution)
Ölçüm metodu:	Colorimetric measurement using pyrocatechol violet method at 578 nm
Ölçüm süresi:	20 min Total Al (dilution + 5 min)
	30 min Total Al & Al (III)
Ortam sıcaklığı:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Parametre:	Aluminum, total
Reaktif gereksinimi:	Keep between 10 - 30 °C
Saptama limiti:	≤ 10 µg/L
Sertifikalar:	CE compliant / ETL certified
Toprak bağlantısı:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²

---

## Kutudakiler

EZ2000 Aluminum Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, and 4 x empty 2.5L Reagent Containers with Fittings 2.5L (for Acid, Buffer, Colour & Mixed Reagent Solution)