



EZ2303 Total Manganese + Manganese Mn(II) Analyser

Ürün Numarası: TRY Fivat: EZ2303.XXXXXXXX Bize Ulaşın

Online colorimetric analysis of Total Manganese + Dissolved Manganese in water

EZ2000 Total Manganese Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low μ g/L range.

EZ2000 Total Manganese Analysers have an internal digestion unit. This additional step prior to analysis allows to measure non-soluble or complexed metal species.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator invervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Total Manganese Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Teknik özellikler

| Ağırlık: | 25 kg |
|--------------------|---|
| Akış Hızı: | 100 - 300 mL/min |
| Alarm : | 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts |
| Analog çıkışlar: | Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option) |
| Boyut (Y x G x D): | 690 mm x 465 mm x 330 mm |
| | |

| Cihaz havası: | Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air |
|----------------------|---|
| Demineralize su: | For rinsing / dilution |
| Dijital çıkışlar: | Optional: Modbus (TCP/IP, RS485) |
| Doğrulama: | Automatic; frequency freely programmable |
| Doğruluk: | Better than 2% full scale range for standard test solutions |
| Drenaj: | Atmospheric pressure, vented, min. $Ø$ 32 mm |
| Enerji: | 230 VAC, 50/60 Hz |
| | |
| | 120 VAC, 50/60 Hz |
| | Max. power consumption: 440 VA |
| Garanti: | 24 aylar |
| Girişimler: | Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar. |
| Kalibrasyon: | Automatic, 2-point; frequency freely programmable |
| Koruma sınıfı: | Protection class: Analyser cabinet: IP44 / Panel PC: IP65 |
| Kutudakiler: | EZ2303 Manganese Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 4 x empty 2.5L Reagent Containers with Fittings (for Acid, Reductor, Buffer, Colour & Mixed Reagent Solution) and 1 x empty 10L Reagent Container with Fittings (for EDTA Solution) |
| Malzeme: | Hinged part: Thermoform ABS, door: PMMA |
| | Wall section: Galvanised steel, powder coated |
| Numune akışı sayısı: | 1, 2, 4 or 8 |
| Numune basıncı: | By external overflow vessel |
| Numune kalitesi: | Maximum particle size 100 μm, < 0.1 g/L; Turbidity < 50 NTU |
| Numune sıcaklığı: | 10 - 30 °C |
| Ölçüm aralığı: | 0.02 - 1 mg/L Mn |
| | |
| | Optional: |
| | 0.004 - 0.1 mg/L |
| | 0.01 - 0.25 mg/L |
| | 0.01 - 0.5 mg/L |
| | 0.16 - 4 mg/L (with internal dilution) |
| | 0.32 - 10 mg/L (with internal dilution) |
| Ölçüm metodu: | Colorimetric measurement using formaldoxime method at 450 nm |
| Ölçüm süresi: | 20 min Total Mn (dilution + 5 min) |
| | 30 min Total Mn & Mn (II) |
| Ortam sıcaklığı: | 10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing) |
| Parametre: | Manganese, total; Mn(II), dissolved |
| Reaktif gereksinimi: | Keep between 10 - 30 °C |
| Saptama limiti: | $\leq 4 \mu g/L$ |
| Sertifikalar: | S 4 μg/L CE compliant / UL certified |
| Toprak bağlantısı: | Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ² |
| ropruk bugunitor. | |

Kutudakiler

EZ2303 Manganese Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 4 x empty 2.5L Reagent Containers with Fittings (for Acid, Reductor, Buffer, Colour & Mixed Reagent Solution) and 1 x empty 10L Reagent Container with Fittings (for EDTA Solution)