



EZ9750 External Dilution Unit, max. 50x dilution, master for 2 analysers

Ürün Numarası:

EZ9750.XX101202

TRY Fiyat:

Bize Ulaşın

Convenient and precise sample dilution up to 1/250 - compatible with EZ Series online analysers

About the EZ9000 Series

The successful implementation of online analysers in process control strategies could not have been achieved without the development of a new generation of automatic sampling and sample preconditioning systems. The EZ9000 Series are the result of many years of experience in filtration, dilution and settling.

The EZ9750 is an external dilution unit designed for sample dilution in water analysis applications where concentrations of the analyte are so elevated that absorbance readings would be out of range, while any internal sample dilution would not be sufficient to cover the broad measuring range. The unit combines a number of features with ease of use:

- Discontinuous sample dilution system for external dilution up to 1/250
- Robust alternative to internal sample dilution by micropump or dispenser
- Dilution with demineralised water
- Fully controlled by analyser panel PC

Teknik özellikler

Ağırlık:	25 kg
Boyut (Y x G x D):	690 mm x 465 mm x 330 mm
Cihaz havası:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Cleaning:	Automatic; frequency freely programmable
Dilution:	Max. 50x dilution

Optional:

Max. 100x

Max.150x

Max. 200x

Max. 250x

Drenaj: 1/4" OD tubing

Enerji:	100 - 240 VAC, 50/60 Hz
Garanti:	Max. power consumption: 120 VA
Koruma sınıfı:	24 aylar
Malzeme:	IP55
	Cabinet: PVC
	Dilution vessel: borosilicate glass
	Tubing: Norprene, PFA, PE
Numune sıcaklığı:	Max. 65 °C
Önemli özellik:	Dilute - Black box with screen
Required fast loop:	100 - 300 mL/min
Size:	Max. 50x dilution
Toprak bağlantısı:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ²