



## EZ1022 Hydrogen Peroxide Analyser

Ürün Numarası:

EZ1022.XXXXXXXXXX

TRY Fiyat:

Bize Ulaşın

### Online colorimetric analysis of Hydrogen Peroxide (H<sub>2</sub>O<sub>2</sub>) in water

EZ1000 Hydrogen Peroxide Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

#### Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

#### Flexibility that meets your needs

EZ Series Hydrogen Peroxide Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

---

### Teknik özellikler

Ağırlık:	25 kg
Akış Hızı:	100 - 300 mL/min
Alarm :	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Analog çıkışlar:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Boyut (Y x G x D):	690 mm x 465 mm x 330 mm
Cihaz havası:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Demineralize su:	For rinsing / dilution

Dijital çıkışlar:	Optional: Modbus (TCP/IP, RS485)
Doğrulama:	Automatic; frequency freely programmable
Doğruluk:	Better than 2% full scale range for standard test solutions
Drenaj:	Atmospheric pressure, vented, min. Ø 32 mm
Enerji:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Garanti:	24 aylar
Girişimler:	Oxidants like Bromine, Bromamine, Chlorine, Copper Cu(II) > 8 mg/L, Chromate, Iodine, Iodoamines, Iron Fe(III) > 20 mg/L, Nitrite, Ozone and Manganese may oxidize the DPD colour solution. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Güç kaynağı:	100 - 240 VAC, 50/60 Hz
Kalibrasyon:	Automatic, 2-point; frequency freely programmable
Koruma sınıfı:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65
Kutudakiler:	EZ1022 Hydrogn Peroxide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and 2 x empty 2.5L Glass Containers with Fittings (for Colour and Buffer Solution)
Malzeme:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: galvanised steel, powder coated
Model:	EZ1022
Numune akışı sayısı:	1, 2, 4, or 8
Numune basıncı:	By external overflow vessel
Numune kalitesi:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Numune sıcaklığı:	10 - 30 °C
Ölçüm aralığı:	5 - 500 µg/L H <sub>2</sub> O <sub>2</sub>
	Optional:
	2 - 125 µg/L
	2 - 250 µg/L
	0.04 - 2.0 mg/L (with internal dilution)
	0.08 - 4.0 mg/L (with internal dilution)
	0.5 - 50 mg/L (with internal dilution)
Ölçüm metodu:	Colorimetric measurement at 510 nm using DPD
Ölçüm süresi:	10 min (dilution + 5 min.)
Ortam sıcaklığı:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Otomatik temizleme:	Evet
Parametre:	Hydrogen Peroxide
Reaktif gereksinimi:	Keep refrigerated.
Saptama limiti:	≤ 2 µg/L
Sertifikalar:	CE compliant / ETL certified
Toprak bağlantısı:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²

## Kutudakiler

EZ1022 Hydrogn Peroxide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and 2 x empty 2.5L Glass Containers with Fittings (for Colour and Buffer Solution)